

Jet Compact 300 D

Portable Suction Unit



Extremely compact suction device to be used to remove fluids from the airway or respiratory support system. The device creates a negative pressure that draws fluids through disposable tubing that is connected to the collection container.

Specific Characteristics

- Light and with small dimensions
- Easy view of the setted vacuum thanks to the led indicators
- Classification ISO High Vacuum/ High Flow

Standard Equipment

- 12V Power cable
- Battery
- Disposable container with filter
- Disposable patient tube

Optional accessories

- SC75011D Jet Compact bag
- SC73017E 220V Power adapter

Compliant with

- ISO 10079-1
- RTCA/DO-160E DO-160E – Section 21 Category M (for battery operation only; commercial aircraft, airborne equipment)

Technical data

Dimensions	245x70x185 mm
Weight	1,60 kg
Vacuum Range	From 50 to 550 mmHg
Flow (free flow)	32 l/min
Noise level	70 dB
Electrical connection requirements	100-240 VAC 47-63 Hz 0,75 A max ; 12VDC 33W max
IP Grade	IP 12
Battery	12V DC Ni-MH
Battery operating time	30 min ON, 30 min OFF
Battery recharging time	5 ore
Container capacity	300 ml
Patient tube lenght	1 m
Operating temp.	From 0°C to +45°C
Storage temp.	From -40°C to +70°C
Umidity	From 0 to 95%

Class IIa Med.Device according to Dir. 93/42/CEE

JET COMPACT 300 D
SC75100D



Registration number 79643

NATO STOCK NUMBER 6515150110085

Distributed by Spencer Italia S.r.l.

Rev.6 (15/01/2018)

UNCHECKED COPY – further revisions will be available on <http://support.spencer.it>
Spencer Italia S.r.l. Sala Baganza (PR) Italia Tel. +39.0521.541111 Fax +39.0521.541222

www.spencer.it